



Material Safety Data Sheet

1 - Chemical Product and Company Identification

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Manufacturer: WD-40 Company Address: 1061 Cudahy Place (92110) P.O. Box 80607 San Diego, California, USA 92138 -0607 Telephone: Emergency only: 1-888-324-7596 (PROSAR) Information: 1-888-324-7596 Chemical Spills: 1-800-424-9300 (Chemtrec) 1-703-527-3887 (International Calls) | Trade Name: WD-40 Specialist™ High Performance White Lithium Grease Chemical Name: Organic Mixture Product Use: Cleaner, Lubricant MSDS Date Of Preparation: 9/05/14 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

2 – Hazards Identification

GHS Classification:

Flammable Aerosol Category 1

Aspiration Toxicity Category 1

**DANGER!**

H222 Extremely Flammable Aerosol.

H229 Pressurized container: may burst if heated.

H304 May be fatal if swallowed and enters airways.

Prevention

P210 Keep away from heat, sparks, open flames, hot surfaces – No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or physician.

P331 Do NOT induce vomiting.

Storage

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents and container in accordance with local and national regulations.

3 - Composition/Information on Ingredients

| Ingredient | CAS # | Weight Percent | GHS Classification |
|-------------------------------|--------------------------|----------------|--------------------------------|
| Petroleum Solvents | 64742-47-8 64742-88-7 | 25-40% | Aspiration Toxicity Category 1 |
| Hydrotreated Heavy Naphthenic | 64742-52-5 | <10% | Not Hazardous |

| | | | |
|--------------------------------------------------------|------------------|--------|--------------------------|
| Distillate | | | |
| Solvent-refined Heavy Paraffinic Petroleum Distillates | 64742-88-4 | <10% | Not Hazardous |
| Titanium Dioxide | 13463-67-7 | <5% | Carcinogen Category 2* |
| Propellant (propane, n-butane) | 74-98-6/106-97-8 | 40-60% | Flammable Gas Category 1 |

* Carcinogen classification applies to respirable forms only. Not applicable to this product.

4 – First Aid Measures

Ingestion (Swallowed): Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

Eye Contact: Flush thoroughly with water. Get medical attention if irritation persists.

Skin Contact: Wash with soap and water. If irritation develops and persists, get medical attention.

Inhalation (Breathing): If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

Most Important Symptoms (acute and delayed): Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. May cause eye, skin and respiratory tract irritation.

Indication of Immediate Medical Attention or Special Treatment: Immediate medical attention is required for ingestion.

5 – Fire Fighting Measures

Extinguishing Media: Use water fog, dry chemical, carbon dioxide or foam. Cool fire exposed containers with water.

Special Fire Fighting Procedures: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

Unusual Fire and Explosion Hazards: Extremely flammable aerosol. Contents under pressure. Keep away from ignition source and open fire. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Flammable liquid and vapor. This material can release flammable vapors when heated above ambient temperatures. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces.

6 – Accidental Release Measures

Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

7 – Handling and Storage

Handling: Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty.

Storage: Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 3 Aerosol.

8 – Exposure Controls/Personal Protection

| Chemical | Occupational Exposure Limits |
|------------------------------------------|-----------------------------------------------------------------------------------|
| Petroleum Solvents | 1200 mg/m ³ TWA Supplier Recommended (total hydrocarbon) |
| Hydrotreated Heavy Naphthenic Distillate | 5 mg/m ³ TWA (inhalable) ACGIH TLV 5 mg/m ³ TWA OSHA PEL |

| | |
|--------------------------------------------------------|--------------------------------------------------------------------------------------|
| Solvent-refined Heavy Paraffinic Petroleum Distillates | 5 mg/m ³ TWA (inhalable) ACGIH TLV 5 mg/m ³ TWA OSHA PEL |
| Titanium Dioxide | 15 mg/m ³ (total dust) TWA OSHA PEL 10 mg/m ³ TWA ACGIH TLV |
| Propane | 1000 ppm TWA OSHA PEL 1000 ppm TWA ACGIH TLV (aliphatic hydrocarbon gas) |
| n-Butane | 1000 ppm TWA ACGIH TLV (aliphatic hydrocarbon gas) |

The Following Controls are Recommended for Normal Consumer Use of this Product

Engineering Controls: Use in a well-ventilated area.

Personal Protection:

Eye Protection: Avoid eye contact. Always spray away from face.

Skin Protection: Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where prolonged skin contact is likely.

Respiratory Protection: None needed for normal use with adequate ventilation.

For Bulk Processing or Workplace Use the Following Controls are Recommended

Engineering Controls: Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

Personal Protection:

Eye Protection: Safety goggles recommended where eye contact is possible.

Skin Protection: Wear chemical resistant gloves.

Respiratory Protection: None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

Work/Hygiene Practices: Wash with soap and water after handling.

9 – Physical and Chemical Properties

| | | | |
|----------------------------------------|----------------------------------------------|-------------------|------------------------------------------|
| Boiling Point: | 221-271°C (430-520°F) (Petroleum Solvent) | Specific Gravity: | 0.87 |
| Solubility in Water: | Insoluble | pH: | Not Applicable |
| Vapor Pressure: | 0.009 kPa (0.07 mm Hg) at 20 C | Vapor Density: | 5.3 (Petroleum Solvent) |
| Percent Volatile: | 76.6% | VOC: | 24.72% |
| Coefficient of Water/Oil Distribution: | Not Determined | Appearance/Odor | Colorless liquid with a petroleum odor. |
| Flash Point: | <-30°C (-22°F) (CC ASTM D3828) | Flammable Limits: | LEL: 0.6% UEL: 5% (Petroleum Solvent) |

10 – Stability and Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Avoid heat, sparks, flames and other sources of ignition.

Incompatibilities: Strong acids, alkalis, and oxidizers.

Hazardous Decomposition Products: Carbon monoxide and carbon dioxide, oxides of nitrogen and sulfur, smoke, fumes, and/or unburned hydrocarbons.

11 – Toxicological Information

Symptoms of Overexposure:

Inhalation: Mist or vapor can irritate the throat and lungs. High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

Skin Contact: May cause skin irritation with short-term exposure with redness, itching and burning of the skin. Prolonged and/or repeated contact may produce defatting and dermatitis.

Eye Contact: Contact may be irritating to eyes. May cause redness, stinging, swelling and tearing.
Ingestion: This product has low oral toxicity. If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.
Chronic Effects: Prolonged or repeated skin contact may defeat the skin resulting in irritation and dermatitis.
Medical Conditions Aggravated by Exposure: Preexisting eye, skin and respiratory conditions may be aggravated by exposure.

Suspected Cancer Agent:

Yes X No

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard. This product contains small amount of titanium dioxide, which is listed by IARC as a suspected carcinogen (Group 2B). Titanium dioxide only presents a risk of cancer by inhalation of very fine dust. In this product, the titanium dioxide is incorporated into the grease and is not present as a respirable dust. There is no exposure to respirable titanium dioxide dust in the normal use of this product. None of the components of this product is considered a reproductive hazard.

12 – Ecological Information

Ecotoxicity: No specific aquatic toxicity data is currently available.

Persistence and Degradability: No data available.

Bioaccumulative Potential: No data available.

Mobility in Soil: No data available

Other Adverse Effects: None known

13 - Disposal Considerations

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Dispose in accordance with federal, state, and local regulations. Do not puncture or incinerate containers.

14 – Transportation Information

DOT Surface Shipping Description: UN1950, Aerosols, 2.1 Ltd. Qty (Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)

IMDG Shipping Description: UN1950, Aerosols, 2.1, LTD QTY

ICAO Shipping Description: UN1950, Aerosols, flammable, 2.1 NOTE: WD-40 does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

15 – Regulatory Information

U.S. Federal Regulations:

CERCLA 103 Reportable Quantity: This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA TITLE III:

Hazard Category For Section 311/312: Acute Health, Fire Hazard, Sudden Release of Pressure

Section 313 Toxic Chemicals: This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

Section 302 Extremely Hazardous Substances (TPQ): None

EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory

VOC Regulations: This product complies with the consumer product VOC limits of CARB, the US EPA and states adopting the OTC VOC rules.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product does not contain chemicals regulated under California Proposition 65. While this product contains titanium dioxide, it is not in a respirable form and is bound in the grease so no exposure occurs under normal conditions of use.

Canadian Environmental Protection Act: All of the ingredients are listed on the Canadian Domestic Substances List or exempt from notification

Canadian WHMIS Classification: Class A (Compressed Gas), Class B-5 (Flammable Aerosol)

This MSDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.

China Regulations on the Control over Safety of Dangerous Chemicals: This product matches this regulation. All ingredients in this product has listed in IECSC(Inventory of Existing Chemical Substances in China 2010)

Korea: All of the components of this product are listed on the Korean chemical inventory.

Philippines: All of the components of this product are listed on the PICCS inventory.

Japan: All of the components of this product are listed on the Japan chemical inventory.

16 – Other Information:

HMIS Hazard Rating:

Health – 1* (slight hazard), Fire Hazard – 4 (severe hazard), Physical Hazard – 0 (minimal hazard)

Revision Date: September, 2014

Supersedes: July, 2014

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA

Approved by: ASM