



# WD-40 SPECIALIST<sup>®</sup> DRY LUBE

## PRODUCT DESCRIPTION

WD-40 Specialist Dry Lube PTFE contains PTFE (polytetrafluoroethylene) which delivers enhanced lubrication and protection, leaving a dry clear film that won't attract dirt, dust and oil. WD-40 Specialist Dry Lube PTFE is also quick drying and great as a mould release agent.

## APPLICATION

- Gears
- Locks
- Tracks
- Chains
- Blades
- Drill Bits
- Power Tools and Equipment
- Hinges

## FEATURES AND BENEFITS

- Withstands temperatures of -45°C to +260°C
- Long lasting lubrication
- Dry film that resist dirt, dust and oil
- Extend the life of tools and equipment
- For use on metals, glass, vinyl, rubber and most plastics

## PHYSICAL AND CHEMICAL PROPERTIES WITHOUT PROPELLANT

BOILING POINT (INITIAL)	98°C
SOLUBILITY IN WATER	Insoluble
4 BALL WEAR	1.0mm (ASTM D4172)
EXTREME PRESSURE	2650 lbs (ASTM D3233)
FLASH POINT	-4°C (ASTM D3828)
APPEARANCE/ODOR	Colorless liquid with a petroleum odor



H2  
REGISTERED  
#148323

## DIRECTIONS

Shake can well before use. Apply by spraying directly on surface to be lubricated and protected. Dries in seconds.

## PACKAGING

PRODUCT NAME	DRY LUBE	UNIT CODE	35004
UNIT SIZE	360 mL	CASE SIZE	12

**NOTE:** The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. WD-40<sup>®</sup> Company specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of WD-40<sup>®</sup> Company products and disclaims any liability for consequential or incidental damages of any kind. Including lost profits.

