





Safety Data Sheet

1 - Chemical Product and Company Identification

Manufacturer:	WD-40 Company	Chemical Name: Mixture
Address:	9715 Businesspark Avenue	
	San Diego, California, USA	Trade Name: WD-40 Low Odour
	92131	
Telephone:	+1-800-448-9340	Product Use: Lubricant, Penetrant, Drives Out
	+1-858-251-5600	Moisture, Removes and Protects Surfaces
Emergency:	1-888-324-7596	From Corrosion
Information:	1-888-324-7596	
Chemical Spills: 1-800-424-9300 (Chemtrec)		SDS Date Of Preparation: October 16, 2020
1-703-5	527-3887 (International Calls)	

2 – Hazards Identification

GHS Classification: Aerosols Category 1 Aspiration Toxicity Category 1

Label Elements:



DANGER!

H222 Extremely flammable aerosol H229 Pressurized container: may burst if heated. H304 May be fatal if swallowed and enters airways.

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use.

Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor. P331 Do NOT induce vomiting.

Storage

P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents and container in accordance with local and national regulations.

3 - Composition/Information on Ingredients

Ingredient	CAS #	Weight Percent	GHS Classification	
C13-16 Isoparaffin	68551-20-2	55-65%	65% Aspiration Toxicity Category 1	
Petroleum Base Oil	Mixture	20-30%	Not Hazardous	
Carbon Dioxide	124-38-9	1-5%	Simple Asphyxiant	

4 – First Aid Measures

Ingestion (Swallowed): Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

Eye Contact: Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists.

Skin Contact: Wash with soap and water. If irritation develops and persists, get medical attention. **Inhalation (Breathing):** Discontinue use and move to fresh air. Get medical attention if irritation develops and persists.

Most Important Symptoms (acute and delayed): Harmful or fatal if swallowed and entered airways. If swallowed, may be aspirated and cause lung damage. May cause eye irritation. Skin contact may cause drying of the skin. Inhalation may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea.

Indication of Immediate Medical Attention or Special Treatment: Immediate medical attention is required for ingestion.

5 – Fire Fighting Measures

Extinguishing Media: Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

Special Fire Fighting Procedures: Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting containers.

Unusual Fire and Explosion Hazards: Extremely flammable aerosol. Contents under pressure. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces. Thermal decomposition will release oxides of carbon, smoke fumes, unburned hydrocarbons.

6 – Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures: Eliminate all sources of ignition and ventilate area. Avoid contact with eyes. Avoid prolonged contact with skin and clothing. Wear appropriate protective clothing (see Section 8).

Environmental Precautions: Report spills to authorities as required.

Methods and Materials for Containment/Cleanup: Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

7 – Handling and Storage

Precautions for Safe Handling: Avoid contact with eyes and skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty.

Conditions for Safe Storage, including any incompatibilities: Store in a cool, well-ventilated area, away from incompatible materials such as oxidizers. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 1 Aerosol.

Chemical	Occupational Exposure Limits			
C13-16 Isoparaffin	None Established			
Petroleum Base Oil	5 mg/m3 TWA (Inhalable) ACGIH TLV (as Mineral oil)			

8 – Exposure Controls/Personal Protection

	3 mg/m3 TWA Japan OEL (as oil mist, mineral)
Carbon Dioxide	5000 ppm TWA, 30,000 ppm STEL ACGIH TLV
	5000 ppm TWA Japan OEL
	5000 ppm TWA, 30,000 ppm STEL Korea OEL
	5000 ppm TWA, 5000 ppm STEL Taiwan OEL

The Following Controls are Recommended for Normal Consumer Use of this Product Engineering Controls: Use in a well-ventilated area.

Personal Protection:

Eye Protection: Avoid eye contact. Always spray away from face.

Skin Protection: Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where prolonged skin contact is likely.

Respiratory Protection: None required.

For Bulk Processing or Workplace Use the Following Controls are Recommended

Engineering Controls: Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

Personal Protection:

Eye Protection: Safety goggles recommended where eye contact is possible.

Skin Protection: Wear rubber gloves and protective clothing as required to avoid prolonged skin contact. **Respiratory Protection:** No respiratory protection normally required. If exposure levels are excessive, wear an approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

Work/Hygiene Practices: Avoid contact with the eyes, skin and clothing. Wash thoroughly after use.

Appearance:	Clear, colorless liquid	Flammable Limits:	Not applicable
Odor:	Weak odor	Vapor Pressure:	Not established
Odor Threshold:	Not established	Vapor Density:	Not established
pH:	Not established	Relative Density:	Not established
Melting/Freezing Point:	Not established	Solubilities:	Insoluble in water
Boiling Point/Range:	>446°F (>230°C)	Partition Coefficient; n-	Not established
		octanol/water:	
Flash Point:	>212°F (>100°C)	Auto ignition	None
		Temperature:	
Evaporation Rate:	Not established	Decomposition	Not established
		Temperature:	
Flammability (solid, gas):	Flammable Aerosol	Viscosity:	Not established
VOC:	Not established	Pour Point:	Not applicable

9 – Physical and Chemical Properties

10 – Stability and Reactivity

Reactivity: Non-reactive

Chemical Stability: Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions: May react with strong oxidizers generating heat.

Conditions to Avoid: Avoid heat, sparks, flames and other sources of ignition. Do not puncture or incinerate containers.

Incompatible Materials: Strong oxidizing agents and strong bases.

Hazardous Decomposition Products: Thermal decomposition will release oxides of carbon, smoke fumes, unburned hydrocarbons.

11 – Toxicological Information

Symptoms of Overexposure:

Inhalation: Mist or vapor can irritate the throat and lungs. High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

Skin Contact: Prolonged and/or repeated contact may produce mild irritation and defatting with possible dermatitis.

Eye Contact: Contact may be irritating to eyes. May cause redness and tearing.

Ingestion: This product has low oral toxicity. If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

Chronic Effects: None currently known.

Carcinogen Status: None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA.

Reproductive Toxicity: None of the components is considered a reproductive hazard.

Numerical Measures of Toxicity:

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg and the dermal toxicity greater than 2,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

12 – Ecological Information

Ecotoxicity: If applied to leaves may kill grasses and small plants by interfering with respiration and transpiration. This product is not toxic to fish but may coat gill structures resulting in suffocation.

Persistence and Degradability: No data available Bioaccumulative Potential: No data available. Mobility in Soil: No data available. Other Adverse Effects: None Known

13 - Disposal Considerations

Aerosol containers should not be punctured, compacted in home trash compactors or incinerated. Empty containers may be disposed of through normal waste management options. Dispose of all waste product, absorbents, and other materials in accordance with applicable Federal, state and local regulations.

14 – Transportation Information

IMDG Shipping Description: UN1950, Aerosols, 2.1, LTD QTY ICAO Shipping Description: UN1950, Aerosols, flammable, 2.1

NOTE: WD-40 Company does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

15 – Regulatory Information

China Regulations on the Control over Safety of Dangerous Chemicals: All ingredients in this product are listed on IECSC (Inventory of Existing Chemical Substances in China 2010).

Korea: This product is authorized for sell in Korea. Please contact WD-40 for more info. **Philippines:** All the components in this product are listed on the Philippines Inventory.

Japan: All the components in this product are listed on the Japanese chemical inventory.

Taiwan: All the components in this product are listed on the Taiwan Inventory.

16 – Other Information

Indication of changes; version 1.0

Training instructions: Not applicable

Further information: The information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Notice to Reader: Employers should use this information only as a supplement to other information gathered by them, and should make independent judgment of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the

product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Revision Date: October 16, 2020

Supersedes: New SDS

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA