



WD-40 SPECIALIST[®] CUTTING OIL

PRODUCT DESCRIPTION

WD-40 Specialist Cutting Oil is a specially formulated blend of lubricants, extreme pressure additives and supplementary components. It is designed to prevent pitting and metal seizures, ease mechanical processing of metals, reducing frictional heat accumulation and frictional forces.

APPLICATION

- Cutting Blade
- Drilling
- Hand Drilling
- Milling
- Tapping
- Threading
- Shearing
- Thread Cutting
- Hand and Power Cutting Equipment

FEATURES AND BENEFITS

- Improves machine finishes and extends tool life
- Reduces cutting torque and improves cutting efficiency
- Suitable for use on all metals
- Provides enhanced lubrication to reduce tip welding
- Contains extreme pressure and anti wear additives



PHYSICAL AND CHEMICAL PROPERTIES WITHOUT PROPELLANT

APPEARANCE	Straw colored liquid in an aerosol can
ODOR	Petroleum Odor
BOILING POINT/RANGE	324°C (616°F)(Petroleum)
FLASH POINT	>165°C (>330°F)(Petroleum)
FLAMMABILITY (SOLID, GAS)	Flammable Aerosol



Nonfood Compounds
Program Listed H2
Registration NSF# 155365

DIRECTIONS

1. Shake can well before use. Hold upright, and spray directly onto the tool and component.
2. Cool cutting surface first before spraying.

PACKAGING

PRODUCT NAME	CUTTING OIL	UNIT CODE	35006
UNIT SIZE	360 mL	CASE SIZE	12

NOTE: The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **WD-40 Company specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of WD-40 Company products and disclaims any liability for consequential or incidental damages of any kind. Including lost profits.**

