



WD-40 SPECIALIST[®] SILICONE

PRODUCT DESCRIPTION

WD-40 Specialist Silicone Lubricant is a non-staining, hardworking formula which provides excellent lubrications without attracting dirt and protects against moisture. It stops parts from sticking and can be used on high pressure equipment.

APPLICATION

- Pipes
- Belts
- Bearings
- Linkages
- Door and Hinges
- Tools
- Guide Rails
- Valves
- Locks and Hoists

FEATURES AND BENEFITS

- Withstands temperatures of -73°C to +260°C
- Prevents parts from sticking
- Waterproofs and protects against moisture
- Excellent lubrication on metal, plastic, rubber and vinyl



H2
REGISTERED
#148324

PHYSICAL AND CHEMICAL PROPERTIES WITHOUT PROPELLANT

BOILING POINT (INITIAL)	228°C
SOLUBILITY IN WATER	Insoluble
4 BALL WEAR	0.60mm (ASTM D4172)
EXTREME PRESSURE	1186 lbs (ASTM D3233)
FLASH POINT	98°C (ASTM D3828)
APPEARANCE/ODOR	Colorless liquid with a petroleum odor

DIRECTIONS

Shake can well before use. Apply by spraying directly on the surface of the object/s to be lubricated and protected.

PACKAGING

PRODUCT NAME	SILICONE	UNIT CODE	35002
UNIT SIZE	360 mL	CASE SIZE	12

NOTE: The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. WD-40[®] Company specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of WD-40[®] Company products and disclaims any liability for consequential or incidental damages of any kind. Including lost profits.

