



## Safety Data Sheet

### 1 - Chemical Product and Company Identification

<b>Manufacturer:</b> WD-40 Company <b>Address:</b> 9715 BusinessPark Ave San Diego, CA , USA <b>Post code:</b> 92131 <b>Telephone:</b> +1-800-448-9340 +1-858-251-5600  <b>24 Hour Emergency Phone Number:</b> 1-888-324-7596 (PROSAR) <b>Chemical Spills:</b> 1-800-424-9300 (Chemtrec) 1-703-527-3887 (International Calls)	<b>Chemical Name:</b> Organic Mixture  <b>Trade Name:</b> WD-40 Bike Dry Chain Lubricant  <b>Product Use:</b> Bike Chain Lubricant  <b>SDS Date Of Preparation:</b> 3/7/16
--	--

### 2 – Hazards Identification

#### GHS Classification:

Flammable Liquid Category 2

Aspiration Toxicity Category 1

Skin Irritant Category 2

Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)



#### DANGER!

H225 Highly Flammable Liquid.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

#### Prevention

P210 Keep away from heat, sparks, open flames, hot surfaces – No smoking.

P233 Keep container tightly closed.

P261 Avoid breathing vapors or mists.

P264 Wash thoroughly with soap and water after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

#### Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or physician.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical attention.

P362 Take off contaminated clothing and wash before reuse.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or physician if you feel unwell.

P370+P378 In case of fire: Use water fog, dry chemical, carbon dioxide or foam to extinguish.

#### Storage

P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.

P405 Store locked up.

#### Disposal

P501 Dispose of contents and container in accordance with local and national regulations.

### 3 - Composition/Information on Ingredients

Ingredient	CAS #	Weight Percent	GHS Classification
Heptane	64742-49-0 142-82-5	40-50%	Aspiration Toxicity Category 1 Flammable Liquid Category 2 Skin Irritant Category 2 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)
Petroleum Base Oil	CBI	30-40%	Not Hazardous
Non-Hazardous Ingredients	CBI	20-30%	Not Hazardous
Cyclohexane	110-82-7	<5%	Aspiration Toxicity Category 1 Flammable Liquid Category 2 Skin Irritant Category 2 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)

### 4 – First Aid Measures

**Ingestion (Swallowed):** Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

**Eye Contact:** Flush thoroughly with water for 15 minutes. Remove contact lenses if present after the first 5 minutes and continue flushing. Get medical attention if irritation persists.

**Skin Contact:** Wash with soap and water. If irritation develops and persists, get medical attention.

**Inhalation (Breathing):** If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

**Most Important Symptoms (acute and delayed):** Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. May cause eye, skin and respiratory tract irritation. Inhalation of vapors may cause irritation, dizziness and drowsiness.

**Indication of Immediate Medical Attention or Special Treatment:** Immediate medical attention is required for ingestion

### 5 – Fire Fighting Measures

**Suitable (and unsuitable) Extinguishing Media:** Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

**Specific Hazards Arising from the Chemical:** Highly flammable liquid and vapor. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. Combustion will produce oxides of carbon, smoke fumes, unburned hydrocarbons. A vapor and air mixture can create an explosion hazard in confined spaces.

**Special Protective Equipment and Precautions for Fire-Fighters:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water.

### 6 – Accidental Release Measures

**Personal Precautions, Protective Equipment and Emergency Procedures:** Wear appropriate protective clothing (see Section 8). Eliminate all sources of ignition and ventilate area.

**Methods and Materials for Containment/Cleanup:** Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

### 7 – Handling and Storage

**Precautions for Safe Handling:** Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children.

**Conditions for Safe Storage:** Store in a cool, well-ventilated area, away from incompatible materials. NFPA 30 Class IB Liquid.

### 8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure Limits
Heptane	400 ppm TWA, 500 ppm STEL ACGIH TLV 400 ppm TWA, 500 ppm STEL Korea OEL
Petroleum Base Oil	5 mg/m <sup>3</sup> (inhalable) TWA ACGIH TLV (as mineral oil)
Non-Hazardous Ingredients	None Established
Cyclohexane	100 ppm TWA ACGIH TLV 200 ppm TWA Korea OEL

#### The Following Controls are Recommended for Normal Consumer Use of this Product

**Engineering Controls:** Use in a well-ventilated area.

**Personal Protection:**

**Eye Protection:** Avoid eye contact. Safety glasses or goggles recommended.

**Skin Protection:** Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where skin contact is likely.

**Respiratory Protection:** None needed for normal use with adequate ventilation.

#### For Bulk Processing or Workplace Use the Following Controls are Recommended

**Engineering Controls:** Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

**Personal Protection:**

**Eye Protection:** Safety goggles recommended where eye contact is possible.

**Skin Protection:** Wear chemical resistant gloves.

**Respiratory Protection:** None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear an approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow local regulations and good Industrial Hygiene practice.

**Work/Hygiene Practices:** Wash with soap and water after handling.

### 9 – Physical and Chemical Properties

Appearance:	Light amber liquid	Flammable Limits: (Solvent Portion)	LEL: 1.0% UEL: 7.0%
Odor:	Mild odor	Vapor Pressure:	45 mmHg @ 20°C
Odor Threshold:	Not established	Vapor Density:	3
pH:	Not Applicable	Relative Density:	0.78 – 0.8
Melting/Freezing Point:	Not established	Solubilities:	Insoluble in water
Boiling Point/Range:	199-210°F (93 - 99°C)	Partition Coefficient; n- octanol/water:	Not established
Flash Point:	15-19°F (-9 - -7°C) ASTM D-93	Autoignition Temperature:	Not established
Evaporation Rate:	Not established	Decomposition Temperature:	Not established
Flammability (solid, gas):	Not Applicable	Viscosity:	4.5 cSt (96 SUS) @ 40°C/100°F

### 10 – Stability and Reactivity

**Reactivity:** Not reactive under normal conditions

**Chemical Stability:** Stable

**Possibility of Hazardous Reactions:** May react with strong oxidizers generating heat.

**Conditions to Avoid:** Avoid heat, sparks, flames and other sources of ignition.

**Incompatible Materials:** Strong oxidizers, acids and bases.

**Hazardous Decomposition Products:** Carbon monoxide and carbon dioxide.

## 11 – Toxicological Information

### Symptoms of Overexposure:

**Inhalation:** High concentrations may cause throat, nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

**Skin Contact:** May cause skin irritation with short-term exposure with redness, itching and burning of the skin. Prolonged and/or repeated contact may produce defatting and possible dermatitis.

**Eye Contact:** Contact may cause moderate eye irritation. May cause redness, stinging, swelling and tearing.

**Ingestion:** This product has low oral toxicity. If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

**Chronic Effects:** Prolonged or repeated skin contact may defeat the skin resulting in irritation and dermatitis.

**Carcinogen Status:** None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA.

**Reproductive Toxicity:** None of the components is considered a reproductive hazard.

### Numerical Measures of Toxicity:

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

## 12 – Ecological Information

**Ecotoxicity:** Heptane: 24 hr LC50 Goldfish – 4 mg/L; 24 hr EC50 Daphnia magna – >10 mg/L  
Cyclohexane: 96 hr Pimephales promelas LC50 – 4.53 mg/L; 24 hr EC50 Daphnia magna – >0.9 mg/L

**Persistence and Degradability:** No data available.

**Bioaccumulative Potential:** No data available.

**Mobility in Soil:** No data available

**Other Adverse Effects:** None know.

## 13 - Disposal Considerations

If this product becomes a waste, it would be expected to meet the criteria of a RCRA ignitable hazardous waste (D001). However, it is the responsibility of the generator to determine at the time of disposal the proper classification and method of disposal. Do not puncture or incinerate containers, even empty. Dispose in accordance with federal, state, and local regulations.

## 14 – Transportation Information

DOT Surface Shipping Description: UN1206, Heptanes, 3, II Ltd. Qty

(Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)

IMDG Shipping Description: UN1206, Heptanes, 3, II LTD QTY

ICAO Shipping Description: UN1206, Heptanes, 3, II

\*Note: Inner packages with less than 5 liters of liquid/ 5 kg of solid are exempt from Marine Pollutant per IMDG Code 2.10.2.7 and ICAO Special Provision A197.

NOTE: WD-40 Company does not test containers to assure that they can withstand the pressure change without leakage when transported by air. We do not recommend that our products be transported by air unless a specific review is conducted.

## 15 – Regulatory Information

### U.S. Federal Regulations:

**CERCLA 103 Reportable Quantity:** This product has an RQ of 20,000 based on the RQ for cyclohexane of 1000 lbs. In addition, oil spills are reportable to the National Response Center under the Clean Water Act. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

### SARA TITLE III:

**Hazard Category For Section 311/312:** Acute Health, Fire Hazard

**Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: Cyclohexane <5%

**Section 302 Extremely Hazardous Substances (TPQ):** None

**EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory.

**California Safe Drinking Water and Toxic Enforcement Act (Proposition 65):** This product does not contain chemicals regulated under California Proposition 65.

### International Regulations:

**Canadian Environmental Protection Act:** One of the components is listed on the NDSL. All of the other ingredients are listed on the Canadian Domestic Substances List or exempt from notification.

**Philippines:** This product contains an ingredient that is not listed on the PICCS. Only limited volumes can be imported. Contact WD40 for more information.

**Korea:** All of the components are listed on the Korean Inventory. This product does not contain toxic or prohibited chemicals.

## 16 – Other Information

### HMIS Hazard Rating:

**Health – 1 (slight hazard), Fire Hazard – 3 (serious hazard), Physical Hazard – 0 (minimal hazard)**

Revision Date: March 7, 2016

Supersedes: January, 2015

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA

1026100/No.