



**SPECIALIST**



## Safety Data Sheet



### 1 - Chemical Product and Company Identification

**Manufacturer:** WD-40 Company  
**Address:** 9715 Businesspark Ave  
 San Diego, CA , USA  
**Post code:** 92131  
**Telephone:** +1-800-448-9340  
 +1-858-251-5600

**24 Hour Emergency Phone Number:**

**1-888-324-7596 (PROSAR)**

**Chemical Spills:**

**1-800-424-9300 (Chemtrec)**

**1-703-527-3887 (International Calls)**

**Chemical Name:** Organic Mixture

**Trade Name:** WD-40 Specialist Machine & Engine Degreaser

**Product Use:** Cleaner, Degreaser

**SDS Date Of Preparation:** Nov 27, 2023

### 2 – Hazards Identification

#### GHS Classification:

Flammable Aerosol Category 1

Aspiration Toxicity Category 1

Eye Irritant Category 2

Skin Irritant Category 3

Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)



#### DANGER!

H222 Extremely Flammable Aerosol.

H229 Pressurized container: may burst if heated.

H304 May be fatal if swallowed and enters airways.

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

#### Prevention

P210 Keep away from heat, sparks, open flames, and hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapors or mists.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear eye protection.

#### Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical attention.

P332+P313 If skin irritation occurs: Get medical attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER or doctor if you feel unwell.

#### Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal**

P501 Dispose of contents and container in accordance with local and national regulations.

**3 - Composition/Information on Ingredients**

Ingredient	CAS #	Weight Percent	GHS Classification
Naphtha (petroleum) hydrotreated light (Contains: Nonane)	64742-47-8 111-84-2	65-75%	Flammable Liquid Category 3 Aspiration Toxicity Category 1 Skin Irritant Category 3 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)
Liquefied Petroleum Gas (propane, n-butane, pentane)	74-98-6 106-97-8 109-66-0	20-30%	Flammable Gas Category 1 Gas Under Pressure, Liquefied gas
Isopropyl Alcohol (Isopropanol)	67-63-0	<5%	Flammable Liquid Category 2 Eye Irritant Category 2 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)
Alcohols, C12-14-secondary, ethoxylated	84133-50-6	<2%	Acute Oral Toxicity Category 4 Acute Inhalation Toxicity Category 4 Skin Irritant Category 2 Eye Damage Category 1

**4 – First Aid Measures**

**Ingestion (Swallowed):** Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately. 24 hours Hotline of Emergency Service for Chemical Incident in China: 0532-83889090.

**Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes, lifting upper and lower eyelids occasionally. Get medical attention if irritation persists.

**Skin Contact:** Wash with soap and water. If irritation develops and persists, get medical attention.

**Inhalation (Breathing):** If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

**Most Important Symptoms (acute and delayed):** Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. May cause moderate eye irritation. May cause mild skin irritation. Prolonged skin contact may cause drying of the skin. Inhalation of mists or vapors may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea.

**Indication of Immediate Medical Attention or Special Treatment:** Immediate medical attention is required for ingestion.

**5 – Fire Fighting Measures**

**Extinguishing Media:** Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

**Special Fire Fighting Procedures:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting containers.

**Unusual Fire and Explosion Hazards:** Contents under pressure. Extremely flammable aerosol. Flammable liquid and vapor. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces.

## 6 – Accidental Release Measures

**Personal Precautions, Protective Equipment and Emergency Procedures:** Eliminate all sources of ignition and ventilate area. Wear appropriate protective clothing (see Section 8).

**Environmental Precautions:** Report spills to authorities as required.

**Methods and Materials for Containment/Cleanup:** Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

## 7 – Handling and Storage

**Precautions for Safe Handling:** Avoid contact with eyes and skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty.

**Conditions for Safe Storage, including any incompatibilities:** Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 3 Aerosol. Store away from oxidizers.

## 8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure Limits
Naphtha (petroleum) hydrotreated light	1200 mg/m <sup>3</sup> TWA Supplier Recommended (total hydrocarbons)
Propane	1000 ppm TWA OSHA PEL
n-Butane	1000 ppm STEL ACGIH TLV
Pentane (all isomers)	500 mg/m <sup>3</sup> TWA, 1000 mg/m <sup>3</sup> STEL People's Republic of China 1000 ppm STEL ACGIH TLV
Isopropanol	350 mg/m <sup>3</sup> TWA, 700 mg/m <sup>3</sup> STEL People's Republic of China 200 ppm TWA, 400 ppm STEL ACGIH TLV 400 ppm TWA OSHA PEL
Nonane	500 mg/m <sup>3</sup> TWA People's Republic of China 200 ppm TWA ACGIH TLV
Alcohols, C12-14-secondary, ethoxylated	None Established

### The Following Controls are Recommended for Normal Consumer Use of this Product

**Engineering Controls:** Use in a well-ventilated area.

**Personal Protection:**

**Eye Protection:** Avoid eye contact. Always spray away from face.

**Skin Protection:** Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where prolonged skin contact is likely.

**Respiratory Protection:** None needed for normal use with adequate ventilation.

### For Bulk Processing or Workplace Use the Following Controls are Recommended

**Engineering Controls:** Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

**Personal Protection:**

**Eye Protection:** Safety goggles recommended where eye contact is possible.

**Skin Protection:** Wear chemical resistant gloves.

**Respiratory Protection:** None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

**Work/Hygiene Practices:** Wash with soap and water after handling.

## 9 – Physical and Chemical Properties

Appearance:	Colorless liquid in an aerosol can	Flammable Limits:	LEL: 0.6% UEL: 12.7%
Odor:	Mild petroleum/solvent odor	Vapor Pressure:	1.57 mmHg @ 20°C (68°F) (Petroleum)
Odor Threshold:	Not established	Vapor Density:	Not established
pH:	Not Applicable	Relative Density:	Not established
Melting/Freezing Point:	Not established	Solubilities:	Negligible in water
Boiling Point/Range:	147-199°C (297-390°F) (Petroleum)	Partition Coefficient; n-octanol/water:	Not established
Flash Point:	≥40°C (≥104°F) (Petroleum)	Autoignition Temperature:	Not established
Evaporation Rate:	Not established	Decomposition Temperature:	Not established
Flammability (solid, gas):	Flammable Aerosol	Viscosity:	Not established
VOC:	Not established	Pour Point:	Not established

## 10 – Stability and Reactivity

**Reactivity:** Not reactive under normal conditions.

**Chemical Stability:** Stable

**Possibility of Hazardous Reactions:** Polymerization will not occur.

**Conditions to Avoid:** Avoid heat, sparks, flames and other sources of ignition. Do not puncture or incinerate containers.

**Incompatible Materials:** Strong oxidizing agents, strong acids and bases.

**Hazardous Decomposition Products:** Carbon monoxide and carbon dioxide, smoke fumes, unburned hydrocarbons.

## 11 – Toxicological Information

### Symptoms of Overexposure:

**Inhalation:** Mist or vapors can irritate the throat and lungs. High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

**Skin Contact:** May cause mild skin irritation with short-term exposure with redness, itching and burning of the skin. Prolonged and/or repeated contact may produce defatting and possible dermatitis.

**Eye Contact:** Contact may cause moderate irritation to eyes. May cause redness, stinging, swelling and tearing.

**Ingestion:** This product has low oral toxicity. If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

**Chronic Effects:** Prolonged or repeated skin contact may defeat the skin resulting in irritation and dermatitis.

**Medical Conditions Aggravated by Exposure:** Preexisting eye, skin and respiratory conditions may be aggravated by exposure.

**Carcinogen Status:** None of the components are listed as a carcinogen or suspect carcinogen by IARC, NTP, ACGIH or OSHA.

**Reproductive Toxicity:** None of the components is considered a reproductive hazard.

### Numerical Measures of Toxicity:

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

## 12 – Ecological Information

**Ecotoxicity:**

Naphtha (petroleum) hydrotreated light: 96 hr Rainbow trout LL50: >1000 mg/L, 48 hr Daphnia magna EL0: 1000 mg/L, 72 hr Pseudokirchneriella subcapitata EL50: >1000 mg/L, 72 hr Pseudokirchneriella subcapitata NOELR: 100 mg/L

**Persistence and Degradability:** Naphtha (petroleum) hydrotreated light: Readily biodegradable- 80% in 28 days.

**Bioaccumulative Potential:** Bioaccumulation is not expected based on an assessment of the ingredients.

**Mobility in Soil:** No data available.

**Other Adverse Effects:** None Known

### 13 - Disposal Considerations

Aerosol containers should not be punctured, compacted in home trash compactors or incinerated. Empty containers may be disposed of through normal waste management options. Dispose of all waste product, absorbents, and other materials in accordance with applicable Federal, state and local regulations.

### 14 – Transportation Information

DOT Surface Shipping Description: UN1950, Aerosols, 2.1 Ltd. Qty

(Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)

IMDG Shipping Description: UN1950, Aerosols, 2.1, LTD QTY

ICAO Shipping Description: UN1950, Aerosols, flammable, 2.1

NOTE: WD-40 Company does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

### 15 – Regulatory Information

**China Regulations on the Control over Safety of Dangerous Chemicals:** All ingredients in this product are listed in the IECSC (Inventory of Existing Chemical Substances in China 2010).

### 16 – Other Information

**Indication of changes:** version 1.0 Amended by GBT16483-2008;

Version 1.1 Company address change

Version 1.2 Component disclosure.

**Training instructions:** Not applicable

**Further information:** The information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

**Notice to Reader:** Employers should use this information only as a supplement to other information gathered by them, and should make independent judgment of suitability of this information to ensure proper use and protect the health and safety of employees. This information is furnished without warranty, and any use of the product not in conformance with this Safety Data Sheet, or in combination with any other product or process, is the responsibility of the user.

Revision Date: Nov 27, 2023

Supersedes: June 2020

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA