



**SPECIALIST**




# Safety Data Sheet



## 1 - Chemical Product and Company Identification

<b>Manufacturer:</b> WD-40 Company <b>Address:</b> 9715 Business Park Ave San Diego, CA , USA <b>Post code:</b> 92131 <b>Telephone:</b> +1-800-448-9340 +1-858-251-5600  <b>24 Hour Emergency Phone Number:</b> 1-888-324-7596 (PROSAR) <b>Chemical Spills:</b> 1-800-424-9300 (Chemtrec) 1-703-527-3887 (International Calls)	<b>Chemical Name:</b> Mixture  <b>Trade Name:</b> WD-40 Specialist Spray Grease  <b>Product Use:</b> Lubricant, Grease  <b>SDS Date Of Preparation:</b> 8/12/16
---	---

## 2 – Hazards Identification

<b>GHS Classification:</b> Flammable Aerosol Category 1 Aspiration Toxicity Category 1 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)

<b>DANGER!</b> H222 Extremely flammable aerosol. H229 Pressurized container: may burst if heated. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness.
<b>Prevention</b> P210 Keep away from heat, sparks, open flames, and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing mist or vapors. P271 Use only outdoors or in a well-ventilated area.
<b>Response</b> P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor. P331 Do NOT induce vomiting. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER or doctor if you feel unwell.
<b>Storage</b> P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
<b>Disposal</b> P501 Dispose of contents and container in accordance with local and national regulations.

## 3 - Composition/Information on Ingredients

Ingredient	CAS #	Weight Percent	GHS Classification
------------	-------	----------------	--------------------

Liquefied Petroleum Gas (propane, n-butane, Isobutane)	68476-86-8	35-45%	Flammable Gas Category 1 Gas Under Pressure, Compressed Gas
Distillates (Petroleum), hydrotreated light (contains Nonane)	64742-47-8 111-84-2	25-35%	Flammable Liquid Category 3 Aspiration Toxicity Category 1 Specific Target Organ Toxicity Single Exposure Category 3 (nervous system effects)
Petroleum Base Oil	64742-56-9 64742-65-0 64742-53-6 64742-54-7 64742-71-8	<20	Not Hazardous

#### 4 – First Aid Measures

**Ingestion (Swallowed):** Aspiration Hazard. DO NOT induce vomiting. Call physician, poison control center or the WD-40 Safety Hotline at 1-888-324-7596 immediately.

**Eye Contact:** Flush thoroughly with water. Remove contact lenses if present after the first 5 minutes and continue flushing for several more minutes. Get medical attention if irritation persists.

**Skin Contact:** Wash with soap and water. If irritation develops and persists, get medical attention.

**Inhalation (Breathing):** If irritation is experienced, move to fresh air. Get medical attention if irritation or other symptoms develop and persist.

**Most Important Symptoms (acute and delayed):** Harmful or fatal if swallowed. If swallowed, may be aspirated and cause lung damage. Prolonged skin contact may cause drying of the skin. Inhalation of mists or vapors may cause nasal and respiratory tract irritation and central nervous system effects such as headache, dizziness and nausea.

**Indication of Immediate Medical Attention or Special Treatment:** Immediate medical attention is required for ingestion.

#### 5 – Fire Fighting Measures

**Extinguishing Media:** Use water fog, dry chemical, carbon dioxide or foam. Do not use water jet or flooding amounts of water. Burning product will float on the surface and spread fire.

**Special Fire Fighting Procedures:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting containers.

**Unusual Fire and Explosion Hazards:** Contents under pressure. Extremely flammable aerosol. Keep away from ignition sources and open flames. Exposure of containers to extreme heat and flames can cause them to rupture often with violent force. Vapors can cause a flash fire. Vapors are heavier than air and may travel along surfaces to remote ignition sources and flash back. A vapor and air mixture can create an explosion hazard in confined spaces.

#### 6 – Accidental Release Measures

**Personal Precautions, Protective Equipment and Emergency Procedures:** Eliminate all sources of ignition and ventilate area. Wear appropriate protective clothing (see Section 8).

**Environmental Precautions:** Report spills to authorities as required.

**Methods and Materials for Containment/Cleanup:** Leaking cans should be placed in a plastic bag or open pail until the pressure has dissipated. Contain and collect liquid with an inert absorbent and place in a container for disposal. Clean spill area thoroughly. Report spills to authorities as required.

#### 7 – Handling and Storage

**Precautions for Safe Handling:** Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use only with adequate ventilation. Keep away from heat, sparks, pilot lights, hot surfaces and open flames. Unplug electrical tools, motors and appliances before spraying or bringing the can near any source of electricity. Electricity can burn a hole in the can and cause contents to burst into flames. To avoid serious burn injury, do not let the can touch battery terminals, electrical connections on motors or appliances

or any other source of electricity. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture, crush or incinerate containers, even when empty.

**Conditions for Safe Storage, including any incompatibilities:** Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. U.F.C (NFPA 30B) Level 3 Aerosol. Store away from oxidizers.

### 8 – Exposure Controls/Personal Protection

Chemical	Occupational Exposure Limits
Propane	1000 ppm TWA OSHA PEL
n-Butane	1000 ppm STEL ACGIH TLV
Isobutane (as butane, all isomers)	1000 ppm STEL ACGIH TLV
Distillates (Petroleum), hydrotreated light	1200 mg/m <sup>3</sup> TWA (manufacturer recommended)
Nonane	200 ppm TWA ACGIH TLV
Petroleum Base Oil	5 mg/m <sup>3</sup> TWA (inhalable) ACGIH TLV (as mineral oil) 5 mg/m <sup>3</sup> TWA OSHA PEL (as oil mist, mineral)

### The Following Controls are Recommended for Normal Consumer Use of this Product

**Engineering Controls:** Use in a well-ventilated area.

**Personal Protection:**

**Eye Protection:** Avoid eye contact. Always spray away from your face.

**Skin Protection:** Avoid prolonged skin contact. Chemical resistant gloves recommended for operations where skin contact is likely.

**Respiratory Protection:** None needed for normal use with adequate ventilation.

### For Bulk Processing or Workplace Use the Following Controls are Recommended

**Engineering Controls:** Use adequate general and local exhaust ventilation to maintain exposure levels below that occupational exposure limits.

**Personal Protection:**

**Eye Protection:** Safety goggles recommended where eye contact is possible.

**Skin Protection:** Wear chemical resistant gloves.

**Respiratory Protection:** None required if ventilation is adequate. If the occupational exposure limits are exceeded, wear a NIOSH approved respirator. Respirator selection and use should be based on contaminant type, form and concentration. Follow OSHA 1910.134, ANSI Z88.2 and good Industrial Hygiene practice.

**Work/Hygiene Practices:** Wash with soap and water after handling.

### 9 – Physical and Chemical Properties

Appearance:	Amber liquid	Flammable Limits:	LEL: 0.7% UEL: 5.6% (Distillates (Petroleum), hydrotreated light)
Odor:	Mild petroleum odor	Vapor Pressure:	Not established
Odor Threshold:	Not established	Vapor Density:	Greater than 1 (air=1)
pH:	Not established	Relative Density:	Not established
Melting/Freezing Point:	Not established	Solubilities:	Insoluble in water
Boiling Point/Range:	>320°F (>160°C)	Partition Coefficient; n-octanol/water:	Not established
Flash Point:	>109°F (>43°C)	Autoignition Temperature:	Not established
Evaporation Rate:	Not established	Decomposition Temperature:	Not established
Flammability (solid, gas):	Flammable Aerosol	Viscosity:	Not established
VOC:	Not established	Pour Point:	Not established

## 10 – Stability and Reactivity

**Reactivity:** Non-reactive

**Chemical Stability:** Stable under normal storage and handling conditions.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Avoid heat, sparks, flames and other sources of ignition. Do not puncture or incinerate containers.

**Incompatible Materials:** Strong oxidizing agents.

**Hazardous Decomposition Products:** Carbon monoxide and carbon dioxide, smoke fumes, unburned hydrocarbons.

## 11 – Toxicological Information

### Symptoms of Overexposure:

**Inhalation:** Mist or vapors can irritate the throat and lungs. High concentrations may cause nasal and respiratory irritation and central nervous system effects such as headache, dizziness and nausea. Intentional abuse may be harmful or fatal.

**Skin Contact:** Prolonged and/or repeated contact may produce mild irritation and defatting with possible dermatitis.

**Eye Contact:** Contact may be irritating to eyes. May cause redness, stinging, swelling and tearing.

**Ingestion:** This product has low oral toxicity. If swallowed, this material may cause irritation of the mouth, throat and esophagus. Swallowing may cause gastrointestinal irritation, nausea, vomiting, diarrhea, dizziness, drowsiness and other central nervous system effects. This product is an aspiration hazard. If swallowed, can enter the lungs and may cause chemical pneumonitis, severe lung damage and death.

**Chronic Effects:** None expected.

**Medical Conditions Aggravated by Exposure:** Preexisting eye, skin and respiratory conditions may be aggravated by exposure.

### Suspected Cancer Agent:

Yes    No X

The oral toxicity of this product is estimated to be greater than 5,000 mg/kg and the dermal toxicity greater than 2,000 mg/kg based on an assessment of the ingredients. This product is not classified as toxic by established criteria. It is an aspiration hazard.

## 12 – Ecological Information

**Ecotoxicity:** No specific aquatic toxicity data is currently available; however components of this product are not expected to be harmful to aquatic organisms

**Persistence and Degradability:** Components are expected to be readily biodegradable.

**Bioaccumulative Potential:** Bioaccumulation is not expected based on an assessment of the ingredients.

**Mobility in Soil:** No data available.

**Other Adverse Effects:** None Known

## 13 - Disposal Considerations

Aerosol containers should not be punctured, compacted in home trash compactors or incinerated. Empty containers may be disposed of through normal waste management options. Dispose of all waste product, absorbents, and other materials in accordance with applicable Federal, state and local regulations.

## 14 – Transportation Information

DOT Surface Shipping Description: UN1950, Aerosols, 2.1 Ltd. Qty

(Note: Shipping Papers are not required for Limited Quantities unless transported by air or vessel – each package must be marked with the Limited Quantity Mark)

IMDG Shipping Description: UN1950, Aerosols, 2.1, LTD QTY

ICAO Shipping Description: UN1950, Aerosols, flammable, 2.1

NOTE: WD-40 Company does not test aerosol cans to assure that they meet the pressure and other requirements for transport by air. We do not recommend that our aerosol products be transported by air.

## 15 – Regulatory Information

### U.S. Federal Regulations:

**CERCLA 103 Reportable Quantity:** This product is not subject to CERCLA reporting requirements, however, oil spills are reportable to the National Response Center under the Clean Water Act and many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

### SARA TITLE III:

**Hazard Category For Section 311/312:** Acute Health, Fire Hazard, Sudden Release of Pressure

**Section 313 Toxic Chemicals:** This product contains the following chemicals subject to SARA Title III Section 313 Reporting requirements: None

**Section 302 Extremely Hazardous Substances (TPQ):** None

**EPA Toxic Substances Control Act (TSCA) Status:** All of the components of this product are listed on the TSCA inventory.

### International Information:

**China Regulations on the Control over Safety of Dangerous Chemicals:** All ingredients in this product are listed in IECSC (Inventory of Existing Chemical Substances in China 2010).

**Korea:** All of the components of this product are listed on the Korean chemical inventory.

**Philippines:** This product contains an ingredient that is not listed on the PICCS. Only limited volumes can be imported. Contact WD40 for more information.

**Japan:** This product contains an ingredient that is not listed on the Japanese chemical inventory.

**Taiwan:** All of the components of this product are listed on the Taiwan chemical inventory.

## 16 – Other Information

### HMIS Hazard Rating:

**Health – 1 (slight hazard), Fire Hazard – 4 (severe hazard), Physical Hazard – 0 (minimal hazard)**

Revision Date: August 2016

Supersedes: July 2016

Prepared by: Industrial Health & Safety Consultants, Inc. Shelton, CT, USA